

# Accu-Lube® LB-4600

## Light Viscosity MQL

### FEATURES

- Economical, light-duty minimum quantity lubricant
- Light-duty machining, sawing and cutting
- Aluminum extrusion machining and sawing
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

### APPLICATIONS

- Light-duty machining, sawing and cutting
- Aluminum extrusion machining and sawing

### DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

### HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

### STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### DISPOSAL

Dispose in accordance with all applicable regulations.



### PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Color	Purple
Odor	Mild
Boiling Point / Range	>302°F (>150°C)
Flash Point	> 302°F (> 150°C)
Pour Point	40°F (4°C)
Specific Gravity	0.86
VOC Content	5.91 g/l
Viscosity	7.3 cSt @ 40°C

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LB4600	1 gal	jug	4	34 lbs
LB4655	55 gal	drum	1	454 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved