

• Excellent on abrasives

FEATURES

- General machining, sawing and cutting
- Post-heat treating aluminum
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- For ferrous & nonferrous metals
- Clean with soap and water

APPLICATIONS

- General machining, sawing and cutting
- Post-heat treating aluminum

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed in a dry and well-ventilated place.

DISPOSAL INFORMATION

Consult the appropriate state, regional, or local regulations for additional requirements.



PHYSICAL PROPERTIES

Appearance/physical state	e Liquid		
Odor	Mild		
Melting point/freezing point	No data available		
Boiling point/range	> 400°F/>204°C		
Vapor pressure	< 1 mmHg		
Partition coefficient	No data available		
Percent volatile	No data available		
Flammability limit	No data available		
Propellant	N/A		
VOC Content	None		
Color	Blue		
Flash point	> 200°F/>93°C		
Relative density	No data available		
Evaporation rate	No data available		
Vapor density	>1		
Auto-ignition temperature	No data available		
Viscosity	No data available		
Specific Gravity (water=1)	0.85		
Temperature Range °F(°C)	No data available		
4-Ball Weld Load	No data available		

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LB5000	1 gallon	Jug	4	34 lbs.
LB5055	55 gal.	Drum	1	425 lbs.

