

# Accu-Lube® LB-5000

## Light Viscosity MQL

### FEATURES

- General machining, sawing and cutting
- Post-heat treating aluminum
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- For ferrous & nonferrous metals
- Clean with soap and water

### APPLICATIONS

- General machining, sawing and cutting
- Excellent on abrasives
- Post-heat treating aluminum

### DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

### HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

### STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### DISPOSAL

Dispose in accordance with all applicable regulations.



### PHYSICAL PROPERTIES

<b>Appearance / Physical State</b>	Liquid
<b>Color</b>	Blue
<b>Odor</b>	Mild
<b>Flash Point</b>	374°F (190°C)
<b>Pour Point</b>	40°F (4°C)
<b>Viscosity</b>	18 cSt @ 40°C

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LB5000	1 gal	jug	4	34 lbs
LB5055	55 gal	drum	1	425 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved