

Accu-Lube® LB-6800

Light Viscosity MQL

FEATURES

- Moderate-duty minimum quantity lubricant
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

APPLICATIONS

- General machining, sawing and cutting
- Sawing aluminum castings

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed in a dry and well-ventilated place

DISPOSAL

Consult the appropriate state, regional, or local regulations for additional requirements.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	Mild
Melting / Freezing Point	No data available
Boiling Point / Range	>400°F/>204°C
Vapor Pressure	<1 mmHg
Partition Coefficient	No data available
Percent volatile	No data available
Flammability	No data available
Propellant	N/A
VOC Content	1.7 g/l
Color	Purple
Flash Point	>400°F/>204°C
Density	No data available
Evaporation Rate	No data available
Vapor density	>1
Auto-Ignition Temperature	No data available
Viscosity	No data available
Specific Gravity	0.93
Temperature Range	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LB6800	1 gal	jug	4	34 lbs
LB6855	55 gal	drum	1	454 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved