

# Accu-Lube® LB-6800

## Light Viscosity MQL

### FEATURES

- Moderate-duty minimum quantity lubricant
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

### APPLICATIONS

- General machining, sawing and cutting
- Sawing aluminum castings

### DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

### HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

### STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### DISPOSAL

Dispose in accordance with all applicable regulations.



### PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Color	Purple
Odor	Mild
Boiling Point / Range	>392°F (>200°C)
Flash Point	> 392°F (>200°C)
Pour Point	-40°F (-40°C)
Specific Gravity	0.93
VOC Content	0.17 % ; 1.72 g/L
Viscosity	9 cSt @ 40°C

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LB6800	1 gal	jug	4	34 lbs
LB6855	55 gal	drum	1	454 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

**800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)**

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved