



LCI

Low-Odor Corrosion Inhibitor



FEATURES

- Prevents rust and corrosion for up to 9 months outdoors and 2 years indoors
- Wax-base coating maintains flexibility after application and self-heals for long-lasting corrosion protection
- Resists dust and debris from adhering to treated surfaces
- Removable, when needed, using LPS solvent degreasers: A-151, F-104°, or PreSolve
- Low-odor formulation for improved worker comfort during application and drying
- Penetrates to displace moisture for deep protection
- Sets in as little as 5 minutes for outdoor storage and stays in place in extreme conditions
- Opaque (non-colored) film applies evenly and protects parts without impacting aesthetics

APPLICATIONS

- For shop application to protect:
 - Heavy machinery and equipment
 - Fabricated metal parts
 - Metal machinery parts

SPECIFICATIONS AND APPROVALS

- NSF International, H2

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
06122	20 oz	trigger bottle	12	18 lbs
06105	5 gal	pail	1	39 lbs
06155	55 gal	drum	1	408 lbs

PROPERTIES

Appearance / Physical State	opaque / liquid
Odor	mild
Percent Volatile	69%
Flammability	lower: 0.7 upper: 5%
VOC Content	69%
Color	opaque white
Flash Point	108°F
Density	6.92 lbs/gal
Vapor Density	heavier than air
Viscosity	400-1200cP
Specific Gravity	0.83 g/mL

DIRECTIONS

Apply on clean surface when possible. Additional applications may be added as needed. Safe to use on fabric, rubber, paint, and other finishes. Easily removed with LPS® A-151 Solvent Degreaser or F-104° Solvent Degreaser.

HANDLING

Do not handle, store, or open near an open flame, sources of heat, or sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

STORAGE

Store locked up. Keep away from heat, sparks, and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved