



DiamondKote™

FOR AVB/NVH & SEALS/GASKETS

DKW-4013D

Silicone free semi-permanent mold release agent designed for application to metallic molds under harsh/high heat conditions for the molding of silicone elastomers.

FEATURES

- Water-based
- Ready-to-use
- Promotes rubber flow
- Excellent for molding of seals, o-rings, and gaskets
- Effective on a variety of peroxide-cured elastomers



EASE OF
RELEASE



INCREASE
MOLD CYCLES



REDUCED
DOWNTIME



HIGHER YIELD



LOWER
DEFECT RATE

APPLICATION INSTRUCTIONS

For best results the surface of the mold must be cleaned prior to application of DiamondKote™ W-4013D. Typical cleaning methods would be media/dry ice blasting or treatment with alkaline detergent followed by neutralization and rinsing with water.

Base Coat: For best results, the tool should be above 100°C (180°C recommended) when applying DiamondKote™ mold release agents. For spray application, utilize an air atomizing spray gun or an airless spray gun which produces a finely atomized spray particle.

1. Thoroughly apply 1st coat, varying the direction of each pass to ensure total tool coverage and sealing. Allow to cure 1:00 min.
2. Repeat step 1 for each additional coat (3 - 4 coats recommended).
3. After the last pass, allow the mold to bake for 5-10 minutes to fully cure and adhere the base coat.
4. Test run to assure mold is clean and assure no transfer of product

Touch-up: Use the same application equipment used for base-coating. Typically a single pass application of the un-diluted material prior to failure of the base coat proves to be effective.



BEST RESULTS ON THESE MATERIALS

SILICONE	FKM	HNBR	EPDM-P
----------	-----	------	--------

PACKAGING DETAILS

PART #	NET CONTENTS	CONTAINER TYPE	COLOR	SHELF LIFE
DKW-4013D-02	5 gal	pail	Translucent Blue	12 Months
DKW-4013D-03	55 gal	drum		



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TO SCHEDULE A DEMO/TEST RUN

800.241.8334 | www.itwprobrands.com/brand/diamond-kote

©2026 ITW Pro Brands • DiamondKote™ is a trademark of Illinois Tool Works • All Rights Reserved • LIDKC1004 • 260605

SCAN FOR
SDS REQUEST





DiamondKote™

***FORMULATED TO ENSURE SMOOTH RELEASE
OF FINISHED PARTS, REDUCING SCRAP AND
OPTIMIZING OVERALL PRODUCTION EFFICIENCY***

