



# LPS<sup>®</sup> DETEX<sup>®</sup> Food Grade Moisture Displacing Spray



## FEATURES

- NSF H1 penetrant can be used anywhere within a facility where incidental food contact may occur
- Multi-purpose, long-lasting formula penetrates, lubricates, displaces water, and protects against corrosion
- Non-toxic, food grade lubricant leaves a thin film to reduce wear on precision components
- Engineered to withstand low temperatures for applications such as coolers and freezers
- Metal and X-ray detectable packaging

## APPLICATIONS

- Blending Machines
- Carton Erectors
- Feed Belts
- Filling Equipment
- Frequent Wash Down Electronic Equipment
- Labeling Stations
- Wrapping Equipment

## SPECIFICATIONS AND APPROVALS

- NSF International, H1
- Halal Product Certified #HP-6516-CH
- Kosher Certified

## PROPERTIES

Appearance / Physical State	Gas.
Color	Clear.
Odor	Characteristic.
Melting / Freezing Point	Not available.
Boiling Point / Range	>338°F (>170°C)
Flash Point	140.0°F (60.0°C) Tag Closed Cup - dispensed liquid
Flammability	Flammable gas.
Vapor Pressure	<1 mm Hg @ 20°C
Vapor Density	>1
Partition Coefficient	<1
Auto-Ignition Temperature	>392°F (>200°C)
Viscosity	< 14 cSt @ 25°C
Explosive Properties	Not explosive.
Oxidizing Properties	Not oxidizing.
Heat of Combustion	> 30 kJ/g
Percent Volatile	20 - 30%
Specific Gravity	0.8 - 0.87 @ 20°C
VOC Content	24%
Dielectric Strength	49 kV (ASTM D1816)

## DIRECTIONS

Shake the can thoroughly before spraying. Hold the can upright and apply 6-12 inches (15-30 cm) from the surface, coating the components thoroughly, paying particular attention to seized contact areas. In severe cases, a second application of the product after several minutes may assist in displacing excess moisture.

## HANDLING

Extremely flammable aerosol. Pressurized container: May burst if heated. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

## STORAGE

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.

## DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

## AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
53016	11 wt oz/312 g/357mL	aerosol	12	12

## METAL DETECTION DETAILS

1. Detection limits for a particular machine depend on a variety of factors including line speed, contaminant placement and orientation, iron fortification (i.e.; flour), wet mode vs. dry mode, fragment size, aperture size, etc. It is the responsibility of the end- user to determine the detection limits of the appropriate DETEX<sup>®</sup> component for the individual line set up and for the particular food product being inspected.
2. Metal and X-ray detection limits for plastic components (above) are based on whole components. Partial plastic and scouring pad components may not be detectable due to detector limitations, partial component size, malfunctioning equipment and/or the type of food product undergoing processing. Scouring pad not X-ray detectable.
3. ITW Pro Brands recommends that all components be tested prior to implementation (separately and included in the processed food product) and/or consult your specific metal detector equipment manufacturer directly.
4. Product shelf life, warranty, and material safety data sheets are available at [www.itwprobrands.com](http://www.itwprobrands.com). ITW Pro Brands is not responsible for use of this product inconsistent with its instructions and warnings.
5. ITW Pro Brands is not responsible for failure to detect components due to detector limitations and/or detector malfunctions. Refer to the metal detector manufacturer's design limitations, instructions, and warnings regarding the use, limitations, and proper maintenance of the equipment.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS<sup>®</sup>, SCRUBS<sup>®</sup>, DYKEM<sup>®</sup>, Accu-Lube<sup>®</sup>, DYMON<sup>®</sup>, Spray Nine<sup>®</sup>, and Cedar<sup>®</sup> are registered trademarks and Rustlick<sup>™</sup>, Diamondkote<sup>™</sup>, and MetalMates<sup>™</sup> are trademarks of Illinois Tool Works • All Rights Reserved