LPS® MAX ChainMate®
Lubricant, Penetrant & Protectant

FEATURES

- Penetrates to protect and lubricate chain pins and linkages
- Moly-based formula protects individual wires within a wire rope in extreme load and temperature applications
- Displaces water that causes chain and wire rope failure
- Anti-sling formulation for less mess
- Conforms to VOC regulations in US and Canada
- Locking flip straw actuator
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

APPLICATIONS

- Bushings
- Cables
- Chains
- Cranes
- Cutting Tools
- Drag Lines
- Drives
- Forklifts
- Pins
- Pulleys & Rollers
- Saws
- Sprockets
- Wire Ropes

SPECIFICATIONS AND APPROVALS

- Ford Motor Co.
- Pratt & Whitney Canada MMC 21530

PROPERTIES

Appearance / Physical State	Black/Liquified Gas
Odor	No odor
Flash Point	Not applicable
Flammability	HIGHLY FLAMMABLE. Upper Limit: 13%, Lower Limit: 2.1%
Water Solubility	Immiscible
Vapor Density	>1, Air = 1
Heat of Combustion	> 30 kJ/g
Density	0.88, Water = 1
Viscosity	150 cSt
Percent Volatile	22%
VOC Content	22%

HANDLING

Safe Handling
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- DO NOT incinerate or puncture aerosol cans.
- DO NOT spray directly on humans, exposed food or food utensils.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within the SDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- NFPA 30B Storage Level: 3

See the SDS for Other Information.

STORAGE

Suitable Container
- Aerosol dispenser.
- Check that containers are clearly labelled.

Storage Incompatibility
- Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances.
- Avoid reaction with oxidizing agents.

DISPOSAL

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.
- Bury residues and emptied aerosol cans at an approved site.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
92416	11 wt oz / 312 g / 405 mL	aerosol	12	12 lbs

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com
LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved