



LPS[®] MAX Electro Contact Cleaner



FEATURES

- New Formula with Lower Global Warming Potential
- Safe on plastics (test for compatibility)
- Fast evaporating formula leaves no residue
- Non-flammable
- Formulated for contact cleaning
- VOC Compliant in all 50 states
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

APPLICATIONS

- Connectors
- Electrical Contacts
- EV Battery Components
- Office Equipment
- Printed Circuit Boards
- Printers
- Relays
- Robotic Systems
- Semiconductors
- Servo Motors
- Solar Cell Components
- Solenoids

SPECIFICATIONS AND APPROVALS

- NSF International, K2

PROPERTIES

Appearance / Physical State	Aerosol. Compressed gas.
Color	Colorless.
Odor	Ether-like.
Melting / Freezing Point	Not available.
Boiling Point / Range	136.4°F (58°C)
Flash Point	None.
Vapor Density	7
Water Solubility	nil.
Specific Gravity	1.21
Percent Volatile	100%
VOC Content	53.4% per US State & Federal Consumer Product Regulations
Dielectric Strength	39.2 kV

DIRECTIONS

Hold can 6-8 inches away and spray directly on surface to clean it. For a directed stream, place the flip straw in the upright position. For a broad area coverage, place the flip straw in the downward position.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

Protect from sunlight. Store in a well-ventilated place. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose of waste and residues in accordance with local authority requirements (see section 13 of SDS).

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
90416	14 wt oz / 397 g	aerosol	12	13.5



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved