



# LPS<sup>®</sup> MAX Instant Super Degreaser

## 2.0-Flammable Industrial Degreaser



### FEATURES

- Does not contain harsh brominated solvents
- Industrial formula for extreme degreasing
- Fast evaporating for quick work
- Non-flammable
- Leaves no residue
- Locking flip straw actuator
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

### APPLICATIONS

- Air Compressors
- Bearings
- Cables
- Chains
- Forklifts
- Gears
- Heavy Equipment
- Power Tools

### SPECIFICATIONS AND APPROVALS

- Airbus UK-ABR 9-0140; Issue 6 Type I
- Boeing D6-17457, Revision T
- NSF International: K1

### PROPERTIES

Appearance / Physical State	Gas
Color	Colorless
Odor	Mild
Flash Point	None - Tag Closed Cup
Vapor Pressure	> 300 mm Hg @ 25°C
Vapor Density	> 1 (air = 1)
Density	11.00
Explosive Properties	None
Oxidizing Properties	None
VOC Content	77.2% per US Federal Consumer Product Regulations
Prop 65 Warning	No

### HANDLING

Pressurized container: do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose container to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not taste or swallow. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink, or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

### STORAGE

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F (49°C) as can may burst. Do not puncture, incinerate, or crush. Do not handle or store near an open flame, heat, or other sources of ignition. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage.

### DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate, or crush. Dispose of contents in accordance with local/regional/national/international regulations.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
97220	20 wt oz / 567 g / 437 mL	aerosol	12	18 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS<sup>®</sup>, SCRUBS<sup>®</sup>, DYKEM<sup>®</sup>, Accu-Lube<sup>®</sup>, DYMON<sup>®</sup>, Spray Nine<sup>®</sup>, and Cedar<sup>®</sup> are registered trademarks and Rustlick<sup>™</sup>, Diamondkote<sup>™</sup>, and MetalMates<sup>™</sup> are trademarks of Illinois Tool Works • All Rights Reserved