



# LPS<sup>®</sup> MAX KB 88

## Maximum Penetrant



### FEATURES

- Heavy duty formulation bites through corrosion to free frozen parts quickly
- Displaces moisture
- Kb solvency value of 151
- Advanced penetration formula frees frozen parts faster
- 22% more penetration and 12.8% more lubricity
- Locking flip straw actuator
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

### APPLICATIONS

- Frozen nuts & bolts
- Chains
- Corroded fasteners
- Equipment disassembly
- Hinges
- Plumbing Fixtures
- Shafts
- Conveyors
- Frozen gears & cogs
- Bearings
- Screws
- Pulleys
- Engines & electric motors
- Relays

### SPECIFICATIONS AND APPROVALS

- NSF International: K1

### PROPERTIES

<b>Appearance / Physical State</b>	Gas
<b>Color</b>	Clear
<b>Odor</b>	Hydrocarbon-like
<b>Flash Point</b>	159.8°F (71.0°C) Tag Closed Cup
<b>Evaporation Rate</b>	<0.1 BuAc
<b>Flammability</b>	Flammable Gas
<b>Vapor Pressure</b>	< 1 mm Hg @ 20°C (est.)
<b>Vapor Density</b>	>1
<b>Auto-Ignition Temperature</b>	>420°F (>215°C)
<b>Density</b>	7.30 lb/gal
<b>Explosive Properties</b>	None
<b>Heat of Combustion</b>	> 30 kJ/g
<b>Oxidizing Properties</b>	None
<b>Percent Volatile</b>	92%
<b>Specific Gravity</b>	0.88 @ 23°C
<b>VOC Content</b>	24% per US State and Federal Consumer Product Regulations
<b>Prop 65 Warning</b>	Yes

### HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

### STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place.

### DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
92316	13 wt oz / 369 g / 417 mL	aerosol	12	12 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS<sup>®</sup>, SCRUBS<sup>®</sup>, DYKEM<sup>®</sup>, Accu-Lube<sup>®</sup>, DYMON<sup>®</sup>, Spray Nine<sup>®</sup>, and Cedar<sup>®</sup> are registered trademarks and Rustlick<sup>™</sup>, Diamondkote<sup>™</sup>, and MetalMates<sup>™</sup> are trademarks of Illinois Tool Works • All Rights Reserved