

# Accu-Lube® LS-10 Paste

## Hand-Applied Lubricants

### FEATURES

- Solid paste lubricant
- Reduces friction for cleaner cutting and better finish
- Vegetable-based lubricant
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

### APPLICATIONS

- Short-run machining
- Burring
- Tapping
- Drilling

### DIRECTIONS

For application on any cutting tool. Apply with brush or immerse tool in paste.

### HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

### STORAGE

Keep container tightly closed in a dry and well-ventilated place

### DISPOSAL

Dispose of in accordance with local regulations.



### PHYSICAL PROPERTIES

Appearance / Physical State	Solid
Odor	Mild
Melting / Freezing Point	110-120°F/43-49°C
Boiling Point / Range	>400°F/>204°C
Vapor Pressure	<1 mmHg
Partition Coefficient	No data available
Percent volatile	No data available
Flammability	No data available
Propellant	N/A
VOC Content	10.07
Color	Blue
Flash Point	>200°F/>93°C
Density	No data available
Evaporation Rate	No data available
Vapor density	>1
Auto-Ignition Temperature	No data available
Viscosity	No data available
Specific Gravity	0.86
Temperature Range	No data available
4-Ball Weld Load	No data available

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
7603	8 fl oz	jar	16	10 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved