



# Magnum

## Premium Lubricant with PTFE



### FEATURES

- High performance, long lasting lubricant with PTFE additives
- Penetrates and protects metal against rust and corrosion up to 1 year indoors
- Extends equipment life
- Performs in extreme conditions
- Safe to use on most surfaces
- Does not contain silicone
- Contoured can for improved hand grip

### APPLICATIONS

- Bearings & Valves
- Cables & Linkages
- Dies, Bits & Fasteners
- Engines & Electric Motors
- Hoists, Lifts & Draglines
- Metal Parts & Hand Tools
- Parts in Storage
- Production & Transportation Equipment
- Pulleys and rollers
- Slides and tracks

### SPECIFICATIONS AND APPROVALS

- NSF International, H2 (Aerosol)
- NSF International, H2 (Bulk)

### PROPERTIES

<b>Appearance / Physical State</b>	Aerosol: Gas, Bulk: Liquid
<b>Color</b>	Brown
<b>Odor</b>	Mild, Sweet.
<b>Boiling Point / Range</b>	383°F (195°C)
<b>Flash Point</b>	174.2°F (79.0°C) Tag Closed Cup - dispensed liquid
<b>Evaporation Rate</b>	< 0.1 BuAc
<b>Flammability</b>	Flammability limit: Lower = 0.6%, Upper = 7%
<b>Vapor Pressure</b>	< 0.05 mm Hg @ 20°C
<b>Vapor density</b>	4.7 (air = 1)
<b>Water Solubility</b>	<4%
<b>Partition Coefficient</b>	< 1
<b>Auto-Ignition Temperature</b>	> 442.4°F (> 228°C)
<b>Viscosity</b>	< 7 cSt @ 25°C
<b>Specific Gravity</b>	0.85 - 0.87 @ 20°C
<b>VOC Content</b>	Aerosol: 2.9%; Bulk: 3.0%
<b>Propellant</b>	Carbon Dioxide
<b>Temperature Range</b>	-60°F - 300°F (-51°C - 149°C)

### DIRECTIONS

Shake well before using. Apply on clean surface when possible. Spray in even coats and reapply as needed.

### HANDLING

DO NOT spray into or around ignition sources. DO NOT allow material to come in contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Avoid breathing vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

### STORAGE

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40°F and 120°F (4.4°C and 49°C). Protect from freezing. Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in a dry, well-ventilated area. Avoid breathing vapors.

### DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
00616	11 wt oz / 312 g / 358 mL	aerosol	12	12 lbs
00605	5 gal / 18.93 L	pail	1	41 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved