



Micro-X

Fast Evaporating Contact Cleaner



FEATURES

- Quick Penetration
- Contains NO Chlorinated solvents
- Fast Drying, No Residue
- NSF Certified: K2 Registration #059853 (aerosol); #059852 (Bulk)
- Safe on metal and plastics

APPLICATIONS

- Circuit Breakers
- Connectors
- Contacts
- Fluid Systems
- Generators
- Instrumentation
- Keyboards
- Magnetic Tap Heads
- Motors
- Terminals
- Office Equipment
- Printed Circuits
- Relays
- Semiconductor Assemblies
- Sensors
- Switch Gears
- Switches
- Telecommunication Equipment
- Telephone Equipment
- TV Tuners

SPECIFICATIONS AND APPROVALS

- NSF International, K2 (Aerosol)
- NSF International, K2 (Non-Aerosol)
- SPECIFICATIONS AND APPROVALS

PROPERTIES

Appearance/physical state	Liquid
Odor	Solvent
Melting point/freezing point	N/A
Boiling point/range	140.9°F (60.5°C)
Vapor pressure	352.53 mm Hg @ 38°C
Partition coefficient	>1
Percent volatile	100%
Flammability limit	lower: 0.6%, upper: 7%
Propellant	Carbon Dioxide
VOC Content	Aerosol: 96.2%; Bulk: 100%
Color	Clear
Flash point	Aerosol: < 1.4°F (< -17.0°C) TCC; Bulk: < -0.4 °F (< -18.0 °C) TCC
Relative density	N/A
Evaporation rate	<1 (Ethyl Ether = 1)
Vapor density	-3 (air = 1)
Auto-ignition temperature	582.8 °F (306°C)
Viscosity	< 3 cSt @ 25°C
Specific Gravity (water=1)	0.64 - 0.67 @ 20°C
Temperature Range °F(°C)	N/A
KB Value	29

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away and spray directly on surface to clean it. DO NOT USE ON ENERGIZED ELECTRICAL EQUIPMENT IN OPERATION AND ALLOW SURFACE TO DRY BEFORE RESTART.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE

Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Protect from freezing.

DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/ or regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
04516	C04516	11 wt. oz./312 g/466 mL	16 oz.	12	12 lbs.
04555	C04555	55 gal. (208 L)	55 gal.	1	308 lbs.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved