



# Multi-Purpose Bearing Grease



## FEATURES

- Ideal for lubricating all types of bearings
- Extends relubrication periods
- Prolongs bearing life
- Excellent load carrying properties
- Good corrosion resistance
- Reduces grease consumption

## APPLICATIONS

- Cement Mixers
- Conveyors
- Elevators
- Gas Extractors
- Motors
- Tray Loaders
- Ventilator Fans

## SPECIFICATIONS AND APPROVALS

- Hazelton Pump
- PlastiPack Packaging
- Universal-Leaf

## PROPERTIES

<b>Color</b>	Blue.
<b>Appearance / Physical State</b>	Solid.
<b>Odor</b>	Not available.
<b>Melting / Freezing Point</b>	Not available.
<b>Boiling Point / Range</b>	640.4°F (338°C)
<b>Flash Point</b>	471.2°F (244.0°C)
<b>Evaporation Rate</b>	Not available.
<b>Vapor Pressure</b>	Not applicable.
<b>Vapor Density</b>	Not applicable.
<b>Density</b>	0.89513 g/cm <sup>3</sup> (7.46986 lbs/gal) (relative density)
<b>Water Solubility</b>	Not available.
<b>Auto-Ignition Temperature</b>	Not available.
<b>Viscosity</b>	140-170 cSt @ 40°C 14 cSt @ 100°C
<b>NLGI Grade</b>	2
<b>Thickener Type</b>	Lithium Complex
<b>Base Oil Type</b>	Mineral Oil
<b>VOC Content</b>	0%
<b>Dropping Point</b>	>500°F
<b>4-Ball Weld Load</b>	500 kg
<b>Timken OK Load</b>	50 lb
<b>Temperature Range</b>	-10°F (-23°C) to 350°F (177°C)
<b>Copper Corrosion</b>	1B

## DIRECTIONS

For use as a high performance, multi-functional bearing grease. Apply either manually or by a suitable applicator. For best results, bearings should be purged of their previous lubricant before introducing new grease.

## HANDLING

Observe good industrial hygiene practices.

## STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

## AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
70614	C70614	14.1 oz / 400 g	cartridge	30	32 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved