



NoFlash[®]

Electro Contact Cleaner



FEATURES

- Non-Flammable
- VOC Compliant in California
- Safe to use on most surfaces, but may be harmful to some plastics
- Quick Penetration
- Removes dirt, moisture, dust, flux, and oxides from internal components of electronic equipment

APPLICATIONS

- Contacts
- Controls
- Instruments
- Meters
- Printed Circuit Boards
- Signals
- Switches
- Sensors
- Telecommunication Equipment

PROPERTIES

Appearance / Physical State	Liquid/Gas
Odor	Strong
Melting / Freezing Point	N/A
Boiling Point / Range	158°F (70°C)
Vapor Pressure	>100 mm Hg @20°C
Partition Coefficient	>1
Percent volatile	100%
Flammability	lower: 4%; upper: 8%
Propellant	HFC-134a
VOC Content	70.1%
Color	Colorless
Flash Point	<73.4°F (< 23.0°C) (TCC)
Density	N/A
Evaporation Rate	6 BuAc
Vapor density	~4.3 (air = 1)
Auto-Ignition Temperature	>914°F (> 490°C)
Viscosity	N/A
Specific Gravity	1.29 - 1.32 @20°C

DIRECTIONS

Hold can 6-8 inches away and spray directly on surface to clean. Test for compatibility on certain plastic surfaces.

HANDLING

Do not handle until all safety precautions have been read and understood. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved