



NoFlash[®] NU

Precision Contact Cleaner



FEATURES

- No Flash Point
- Aggressive non-flammable solvent used to clean electronic or precision equipment
- Safe to use on most surfaces, but may be harmful to some plastics
- Quick penetration
- No Rinsing
- Available in Canada Only

APPLICATIONS

- Contacts
- Controls
- Instruments
- Meters
- Printed Circuit Boards
- Signals
- Switches
- Sensors
- Telecommunication Equipment

PROPERTIES

Appearance / Physical State	Gas
Odor	Strong
Melting / Freezing Point	N/A
Boiling Point / Range	158°F (70°C)
Vapor Pressure	> 100 mm Hg @20°C
Partition Coefficient	>1
Percent volatile	100%
Flammability	lower: 4%; upper: 8%
Propellant	HFC-134a
VOC Content	70.1%
Color	Colorless
Flash Point	< 73.4°F (< 23.0°C) (TCC)
Density	N/A
Evaporation Rate	6 BuAc
Vapor density	-4.3 (air = 1)
Auto-Ignition Temperature	> 914 °F (> 490°C)
Viscosity	N/A
Specific Gravity	1.29 - 1.32 @20°C

DIRECTIONS

Hold can 15-20 cm (6-8 inches) away and spray directly on surface to clean.

HANDLING

Do not handle until all safety precautions have been read and understood. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

DISPOSAL

Dispose of content/container in accordance with local/regional/national/international regulation.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
	C04015	12 wt oz / 340 g / 268 mL	aerosol	12	15 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved