



OCX CITRUS DEGREASER



FEATURES

- High performance industrial degreaser that cleans on contact
- No chlorinated solvents
- Safe on all metals and most plastics
- Flash point above 100°F (38°C)
- Natural based
- Fast acting on grease, oil, and grime
- Safe on all metals and most plastics
- Non-conductive
- Inverta Spray Valve lets you spray in an upright or inverted position

APPLICATIONS

- Air Compressors
- Bearings
- Chains & Cables
- Cranes
- Engines
- Forklifts

PROPERTIES

Appearance / Physical State	Gas/Aerosol - Liquid/Bulk
Odor	Mild Citrus
Melting / Freezing Point	Not established
Boiling Point / Range	> 314.6°F (> 157°C)
Vapor Pressure	< 5 mm Hg @ 20°C
Partition Coefficient	>1
Percent volatile	100%
Flammability	Not available
Propellant	Carbon dioxide
VOC Content	(Aerosol) 97.2%, (Bulk) 100% per US State and Federal Consumer Product Regulations
Color	Clear water-white
Flash Point	104.0°F (40.0°C) Tag Closed Cup (dispensed liquid)
Density	Not available
Evaporation Rate	0.2 (BuAc = 1)
Vapor density	> 1 (air = 1)
Auto-Ignition Temperature	> 392°F (> 200°C)
Viscosity	< 3 cSt
Specific Gravity	0.82 - 0.86 @ 20°C
Water Solubility	Slightly soluble in water
Temperature Range	Not available
4-Ball Weld Load	Not applicable

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Aerosol - Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. (see Section 7 of the SDS)

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. (see Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved