



OVS 210-21

Stamping Lubricant

METAL MATES OVS 210-21 is a heavy duty lubricant for stamping, piercing, and punching.

FEATURES

- Provides excellent tool life
- Can dilute wide range
- Can be welded without wash
- Will not build up in dies

APPLICATIONS

- Spray, brush, roll coat or drip. Good on multiple substrates, please call for consultation on specific applications.

DIRECTIONS

Dilute Metal Mates OVS with water to suit the specific application. NOTE: These dilution ratios should only be used as general guidelines and are not exact specifications. Please contact your Metal Mates Regional Sales Manager for an application specific

HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

DISPOSAL

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



PROPERTIES

Odor	mild
pH Value	8.3-9.3
Specific Gravity	0.98
Flash Point	>200F (>93C)
Boiling Point / Range	212F (100C)
Vapor Pressure	<1
Vapor Density	Heavier than air
Prop 65 Warning	No
Total Chlorine	Y
Dilution Ratio	Typical Dilution: 3:1 to 6:1 (33-17%)

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
MM2002	5 gal	pail	1	creamy tan
MM2003	55 gal	drum	1	creamy tan
MM2006	330 gal	tote	1	creamy tan



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved