



PF-141 IG

Industrial Grade Solvent



FEATURES

- Non-corrosive to metals such as copper, aluminum, magnesium, and stainless steel
- Will not attack most commercial resins, plastics, urethanes, and synthetic rubbers
- Excellent for use in parts washers
- No ozone depletion potential
- Flash point above 140°F (60°C)
- Non-conductive
- Removes petroleum based oils such as stamping oils, cutting fluids, rust inhibitors, and cable pulling lubricants

APPLICATIONS

- Air compressors
- Aircraft structures
- Cables
- Chains
- Coils
- Cowlings
- Cranes
- Gears
- Landing gear
- Motors
- Truck booms
- Turbines

SPECIFICATIONS AND APPROVALS

- AMS 1526B
- ARP 1755B
- Boeing D6-17487 Rev. L
- McDonnell Douglas CSD #1
- MIL-PRF-680B Type II

PROPERTIES

Appearance/physical state	Liquid
Odor	Mild Hydrocarbon-like
Melting point/freezing point	Not established
Boiling point/range	365 - 411.8°F (185 - 211°C)
Vapor pressure	0.48 mm Hg @ 20°C
Partition coefficient	Not determined
Percent volatile	100%
Flammability limit	Flammability limit - lower (%) 0.7% Flammability limit - upper (%) 5.3%
Propellant	Not applicable
VOC Content	100 % per US State & Federal Consumer Product Regulations
Color	Clear water-white
Flash point	> 141.8°F (> 61.0°C) Tag Closed Cup
Relative density	Not available
Evaporation rate	< 0.1 BuAc = 1
Vapor density	5.6 (air = 1)
Auto-ignition temperature	635°F (335°C)
Viscosity	1.99 cSt @ 25°C
Specific Gravity (water=1)	0.74 - 0.78 @20°C
Solubility (water)	Negligible
Temperature Range °F(°C)	Not available
4-Ball Weld Load	Not applicable

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. (see Section 7 of the SDS)

STORAGE

Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. (see Section 7 of the SDS)

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
62855	C62855	55 gal / 208 L	drum	1	383 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved