



# PF-HP

## HIGH PERFORMANCE SOLVENT



### FEATURES

- Heavy duty, penetrating degreaser that removes grease and oil
- Specially formulated for power utility applications
- Compatible with power cable and power cable components
- Excellent for use in part washers and dip tanks
- No ozone depletion potential
- Flash point above 140°F (60°C)
- Nonconductive
- No residue
- Does not contain chlorinated solvents
- No ozone depletion potential

### APPLICATIONS

- Aerospace
- Coils
- Motors
- Power Cables
- Transformers
- Turbines

### PROPERTIES

<b>Appearance / Physical State</b>	Liquid
<b>Odor</b>	Characteristic
<b>Melting / Freezing Point</b>	Not established
<b>Boiling Point / Range</b>	320°F (160°C)
<b>Vapor Pressure</b>	> 0.1 mm Hg @ 20°C
<b>Partition Coefficient</b>	Not established
<b>Percent volatile</b>	100%
<b>Flammability</b>	Flammability limit - lower (%) 0.7% Flammability limit - upper (%) 11.7%
<b>Propellant</b>	Not applicable
<b>VOC Content</b>	100% per US State and Federal Consumer Product Regulations
<b>Color</b>	Colorless
<b>Flash Point</b>	> 141.8°F (> 61.0°C) Tag Closed Cup
<b>Density</b>	Not available
<b>Evaporation Rate</b>	0.1 (BuAc = 1)
<b>Vapor density</b>	> 1 (air = 1)
<b>Auto-Ignition Temperature</b>	500°F (260°C)
<b>Viscosity</b>	Not established
<b>Specific Gravity</b>	0.85 - 0.87 @ 20°C
<b>Water Solubility</b>	Not soluble in water
<b>Temperature Range</b>	Not available
<b>4-Ball Weld Load</b>	Not applicable

### DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

### HANDLING

Do not smoke while using or until sprayed surface is thoroughly dry. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. (see Section 7 of the SDS)

### STORAGE

Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. (see Section 7 of the SDS)

### DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

**800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)**

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved