



## FEATURES

- A full strength, penetrating degreaser that removes grease and oil
- Can be used in parts washers, dip tanks, and ultrasonic cleaners
- Does not contain chlorinated solvents such as trichloroethylene or perchloroethylene
- Flash point above 140°F (60°C)
- Compatible with power cables and components
- Specially formulated for power utility applications
- Safe to use on most surfaces

## APPLICATIONS

- Aircraft
- Bonding prep
- Coils
- Cowlings
- Generators
- Landing gear
- Motors
- Power cables
- Transformers
- Turbines

## SPECIFICATIONS AND APPROVALS

- ARP 17558
- ASTM F-945
- Boeing D6-17487 rev. T
- McDonnell Douglas CSD #1
- MIL-PRF-680C Type IV

## PROPERTIES

<b>Appearance / Physical State</b>	Gas/Aerosol - Liquid/Bulk
<b>Odor</b>	Orange
<b>Melting / Freezing Point</b>	Not established
<b>Boiling Point / Range</b>	365°F (185°C) @760 mm Hg
<b>Vapor Pressure</b>	0.48 mm Hg @ 20°C
<b>Partition Coefficient</b>	Not determined
<b>Percent volatile</b>	100%
<b>Flammability</b>	Not available
<b>Propellant</b>	Carbon dioxide
<b>VOC Content</b>	(Aerosol) 97.2%, (Bulk) 100% per US State and Federal Consumer Product Regulations
<b>Color</b>	Clear water-white
<b>Flash Point</b>	> 141.8°F (> 61.0°C) Tag Closed Cup
<b>Density</b>	Not available
<b>Evaporation Rate</b>	< 0.1 BuAc = 1
<b>Vapor density</b>	> 1 (air = 1)
<b>Auto-Ignition Temperature</b>	635°F (335°C)
<b>Viscosity</b>	1.5 cSt @ 25°C
<b>Specific Gravity</b>	0.74 - 0.78 @20°C
<b>Water Solubility</b>	Negligible
<b>Temperature Range</b>	Not available
<b>4-Ball Weld Load</b>	Not applicable

## DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

## HANDLING

Aerosol - Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Bulk - Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices (see Section 7 of the SDS).

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. (see Section 7 of the SDS)

## DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

## AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
61400	1 towel	packet	144	6 lbs
61410	1 wet/dry towel	packet	144	5 lbs
61420	14 wt oz / 397 g / 516 mL	aerosol	12	15 lbs
61432	32 fl oz / 946 mL	bottles	12	22 lbs
61401	1 gal / 3.78 L	can	4	31 lbs
61405	5 gal / 18.93 L	pail	1	37 lbs
61456	55 gal / 208 L	drum	1	383 lbs