



Plastic Safe Electrical Cleaner



FEATURES

- Safe on plastics
- Fast Evaporating formula that leaves no residue
- Non-Flammable
- Formulated for contact cleaning
- NSF Certified: K2 Registration #129002
- VOC Compliant in all 50 states

APPLICATIONS

- Connectors
- Electrical Contacts
- Magnetic Heads
- Office Equipment
- Printed Circuit Boards
- Printers
- Relays
- Solenoids

SPECIFICATIONS AND APPROVALS

- Cessna Approval #244689
- General Motors Co.
- Inland Steel
- Kimberly-Clark
- Minntac - US Steel
- NSF International, K2

PROPERTIES

Appearance/physical state	Liquid/Aerosol
Odor	Mild, Ether-like
Melting point/freezing point	N/A
Boiling point/range	383°F (195°C)
Vapor pressure	Not Determined
Partition coefficient	<1
Percent volatile	100%
Flammability limit	N/A
Propellant	HFC-134a
VOC Content	30.6% per California Consumer Product Regulations, 11.6% per other US State & Federal Consumer Product Regulations
Color	Consumer Product Regulations
Flash point	None (TCC)
Relative density	N/A
Evaporation rate	> 1 (Ethyl Ether =1)
Vapor density	N/A
Auto-ignition temperature	Not Determined
Viscosity	< 3 cSt @ 25°C
Specific Gravity (water=1)	1.34 @ 25°C

DIRECTIONS

DO NOT use on energized electrical equipment or equipment in operation and allow surface to dry before restart. Hold can 6-8 inches away and spray directly on surface to clean. Test on a small inconspicuous area or similar expendable component prior to use to assure material compatibility. Lubricate and protect the clean surface with your choice of LPS® lubricants and corrosion inhibitors.

HANDLING

DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists. Avoid contact with eyes, skin, and clothing. Ground and bond containers before transferring materials.

STORAGE

Keep container in a cool, dry, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

DISPOSAL INFORMATION

Dispose of contents in accordance to local/state/national waste disposal regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
04620	C04620	18 wt.oz./510 g/412 mL	Aerosol	12	18 lbs.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved