



# Plastic Safe Electrical Cleaner



## FEATURES

- Safe on plastics
- Fast Evaporating formula that leaves no residue
- Non-Flammable
- Formulated for contact cleaning
- NSF Certified: K2 Registration #129002
- VOC Compliant in all 50 states

## APPLICATIONS

- Connectors
- Electrical Contacts
- Magnetic Heads
- Office Equipment
- Printed Circuit Boards
- Printers
- Relays
- Solenoids

## SPECIFICATIONS AND APPROVALS

- Cessna Approval #244689
- General Motors Co.
- Inland Steel
- Kimberly-Clark
- Minntac - US Steel
- NSF International, K2

## PROPERTIES

<b>Appearance / Physical State</b>	Liquid/Aerosol
<b>Odor</b>	Mild, Ether-like
<b>Melting / Freezing Point</b>	N/A
<b>Boiling Point / Range</b>	383°F (195°C)
<b>Vapor Pressure</b>	Not Determined
<b>Partition Coefficient</b>	<1
<b>Percent volatile</b>	100%
<b>Flammability</b>	N/A
<b>Propellant</b>	HFC-134a
<b>VOC Content</b>	30.6% per California Consumer Product Regulations, 11.6% per other US State & Federal Consumer Product Regulations
<b>Color</b>	Consumer Product Regulations
<b>Flash Point</b>	None (TCC)
<b>Density</b>	N/A
<b>Evaporation Rate</b>	> 1 (Ethyl Ether =1)
<b>Vapor density</b>	N/A
<b>Auto-Ignition Temperature</b>	Not Determined
<b>Viscosity</b>	< 3 cSt @ 25°C
<b>Specific Gravity</b>	1.34 @ 25°C

## DIRECTIONS

DO NOT use on energized electrical equipment or equipment in operation and allow surface to dry before restart. Hold can 6-8 inches away and spray directly on surface to clean. Test on a small inconspicuous area or similar expendable component prior to use to assure material compatibility. Lubricate and protect the clean surface with your choice of LPS® lubricants and corrosion inhibitors.

## HANDLING

DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists. Avoid contact with eyes, skin, and clothing. Ground and bond containers before transferring materials.

## STORAGE

Keep container in a cool, dry, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

## DISPOSAL

Dispose of contents in accordance to local/state/national waste disposal regulations.

## AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
04620	C04620	18 wt oz / 510 g / 412 mL	aerosol	12	18 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved