

Accu-Lube® Power Stamp II

Light Viscosity MQL

FEATURES

- Superior, heavy-duty minimum quantity lubricant with non-chlorinated extreme pressure and anti-wear additives.
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating

APPLICATIONS

- Operations that generate a lot of heat
- Stamping
- Machining aluminum and titanium
- For ferrous & nonferrous metals, aluminum and titanium
- Carbide die stamping

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling

STORAGE

Store at 10-49°C/50-120°F. Keep container tightly closed

DISPOSAL

Dispose of in accordance with local/regional/national regulations



PHYSICAL PROPERTIES

| | |
|-----------------------------|-------------------|
| Appearance / Physical State | Liquid |
| Odor | Mild |
| Melting / Freezing Point | No data available |
| Boiling Point / Range | >400°F/>204°C |
| Vapor Pressure | < 1 mmHg |
| Partition Coefficient | No data available |
| Percent volatile | No data available |
| Flammability | No data available |
| Propellant | N/A |
| VOC Content | None |
| Color | Purple |
| Flash Point | No data available |
| Density | No data available |
| Evaporation Rate | No data available |
| Vapor density | >1 |
| Auto-Ignition Temperature | No data available |
| Viscosity | No data available |
| Specific Gravity | 0.91 |
| Temperature Range | No data available |
| 4-Ball Weld Load | No data available |

AVAILABLE PRODUCTS

| Part No. | Net Contents | Container Type | Units/Case | Case Weight |
|----------|--------------|----------------|------------|-------------|
| LBSTII01 | 1 gal | jug | 4 | 34 lbs |
| LBSTII55 | 55 gal | drum | 1 | 470 lbs |



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved