

Accu-Lube® Power Stamp III

General Purpose MQL

FEATURES

- Vegetable-based, biodegradable lubricant
- Water-washable
- Clean before heat treating with rinse water
- Heavy-duty

APPLICATIONS

- Carbide die stamping
- Drawing and fine blanking
- Stamping sheet metal up to 0.125" thick (gauge 8 and higher, depending on the type of metal)
- For ferrous & nonferrous metals, aluminum and titanium

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed in a dry and well-ventilated place.

DISPOSAL INFORMATION

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	No data available
Boiling point/range	>400°F/>204°C
Vapor pressure	<1 mmHg
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	No data available
Color	Golden
Flash point	>400°F/>204°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	>1
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.935
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LBSTIII01	1 gal	bottle	4	34 lbs
LBSTIII55	55 gal	drum	1	459 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved