



Premium Leak Detector



FEATURES

- Identifies gas and air leaks quickly
- Bubbles when exposed to gas leaks
- Meets or exceeds strict Telco performance specs
- No ethylene glycol
- Non-Toxic, Non-Hazardous, and Non-Flammable
- Available in Ready-To-Use and Concentrated Formula

APPLICATIONS

- Air Locks
- Air Pipes
- Air Tools
- Air Hose
- Compressors
- Fittings and Connectors
- Gas Appliances
- Lead Cable Sheath
- Natural Gas Meters
- Pneumatic Pipe and Ducts
- Propane Tanks
- Polyethylene Cable Sheath
- Refrigeration Equipment
- Sleeves & Splice Cases

PROPERTIES

Appearance / Physical State	Liquid
Odor	Odorless
Melting / Freezing Point	N/A
Boiling Point / Range	N/A
Vapor Pressure	18 mm Hg @ 20°C
Partition Coefficient	> 1
Flammability	N/A
VOC Content	0%
Color	Colorless
Flash Point	None
Density	1.00 - 1.10 @ 20°C
Evaporation Rate	1 (water = 1)
Vapor density	> 1 (air = 1)
Auto-Ignition Temperature	N/A
Viscosity	< 3 cSt @ 25°C
Water Solubility	100% in water
Temperature Range	10oF or higher
Specific Gravity	1.02 - 1.05
pH Value	6 - 8

DIRECTIONS

DILUTIONS: 10°F - 20°F = 1 Gallon concentrate with 1 gallon of tap water. Above 20°F = 1 Gallon concentrate with 2 gallons of tap water. Use according to standard company practice. Spray, brush, wipe, or pour product onto desired area. Formation of bubbles indicates leaking.

HANDLING

Observe good industrial hygiene practices. Wash hands after handling. The use of goggles is recommended.

STORAGE

Store away from incompatible materials. Keep away from children.

DISPOSAL

Dispose of waste and reissues in accordance with local authority requirements. To avoid slipping injury, contain/absorb spill with inert material, then place in suitable waste container.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
61006	1 gal / 3.78 L (concentrate)	bottle	4	38 lbs
61016	16 fl oz / 473 mL	bottle	12	14 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved