



QB Precision Duster



FEATURES

- Non-flammable, odorless, and leaves no residue
- Blasts away contaminants, dirt, dust, and other soils
- Excellent for use on delicate mechanisms and energized electrical equipment
- Moisture free
- Removes contaminants, dirt, dust, and other soils
- New Propellant with Lower Global Warming Potential
<i>Global Warming Potential 100-yr rev. 5 IPCC (GWP CO₂ = 1):
Previous propellant (HFC-134a) = 1300
New propellant (HFO-1234ze) = <1</i>

APPLICATIONS

- Assemblies
- Avionics
- Circuit boards
- Computers
- Connectors
- Controls
- Data Processing Equipment
- Electronic Contacts
- Electronic Equipment
- Industrial Magnetic Tape Instrumentation Heads
- Keyboards
- Laboratory Instruments
- Office Equipment
- Printed Circuits
- Semiconductors
- Switches
- Telephone Equipment

PROPERTIES

Appearance / Physical State	Gas
Color	Colorless
Odor	Slight. Ether-like.
Melting / Freezing Point	Not available.
Boiling Point / Range	-2.2 °F (-19 °C)
Flash Point	Not applicable.
Evaporation Rate	Not applicable.
Flammability	Lower Explosive limit (%): None at 20°C; 5.7 % at 60°C Upper Explosive limit (%): None at 20°C; 11.3 % at 60°C
Vapor Pressure	4271 hPa @ 20°C (68°F) 11152 hPa @ 54.4°C (129.9°F)
Vapor Density	4
Density	Not available.
Water Solubility	0.37 g/l @ 25°C
Partition Coefficient	> 1
Auto-Ignition Temperature	694.4°F (368°C)
Viscosity	Not established.
Heat of Combustion	< 20 kJ/g
Percent volatile	100%
Specific Gravity	1.17 @ 21.1°C
VOC Content	0% per State & Federal Consumer Product Regulations
Propellant	HFO-1234ze

DIRECTIONS

Hold can in upright position. Spray in short bursts until contaminants are removed. Do not tilt, invert or shake can during use. For precision applications, use attached extension tube.

HANDLING

Avoid breathing vapors. Avoid skin contact with liquid product. Vapors are heavier than air. Keep out of reach of children.

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Store aerosols as Level 1 Aerosol (NFPA 30B).

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
05710	C05710	12 wt oz / 340 g / 281 mL	aerosol	12	11 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved