

FEATURES

- Ideal for removing dirt, moisture, flux, or oxides from the internal components of electronic equipment
- Quick, Penetration with no rinsing
 Non-Flammable/Fast Evaporation/Non-Conductive
- Does not contain brominated solvents; Unique alternative to HCFC
- NSF Certified: K2 Registration #140245
- VOC Compliant in all 50 states

APPLICATIONS

- Contacts
- Controls
- Instruments
- Meters
- Printed Circuit Boards
- Signals
- Switches
- Sensors
- Telecommunication Equipment

SPECIFICATIONS AND APPROVALS

• Canadian Food Inspection Agency • NSF International, K2

PROPERTIES

Gas		
Mild		
N/A		
107.6°F (42°C)		
868 mm Hg @20°C		
N/A		
100%		
N/A		
HFC-134a		
64.7% per US State and Federal Consumer Product Regulations		
Colorless		
None		
N/A		
< 1 BuAc		
> 1		
860°F (460°C) estimated		
<3 cSt @ 25°C		
1.2 - 1.3 @20°C		
47,500 V		
60		

DIRECTIONS

Hold can 6-8 inches away and spray directly on surface to clean. While safe to use on most surfaces, test for compatibility in an inconspicuous area before applying generally.

HANDLING

Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection.

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect

DISPOSAL INFORMATION

Dispose of contents/container in accordance to local/state/national waste disposal regulations.

AVAILABLE PRODUCTS

Part No.		Note Company	C	Unite /Cons	Const. Walnut
US	Canada	Net Contents	Container Type	Units/Case	Case Weight
04416	C04416	12 wt.oz./340 g/279 mL	Aerosol	12	13 lbs.

