



REVO 66[®]

Contact Cleaner



FEATURES

- Ideal for removing dirt, moisture, flux, or oxides from the internal components of electronic equipment
- Quick, Penetration with no rinsing
- Non-Flammable/Fast Evaporation/Non-Conductive
- Does not contain brominated solvents; Unique alternative to HCFC cleaners
- NSF Certified: K2 Registration #140245
- VOC Compliant in all 50 states

APPLICATIONS

- Contacts
- Controls
- Instruments
- Meters
- Printed Circuit Boards
- Signals
- Switches
- Sensors
- Telecommunication Equipment

SPECIFICATIONS AND APPROVALS

- Canadian Food Inspection Agency
- NSF International, K2

PROPERTIES

Appearance / Physical State	Gas
Odor	Mild
Melting / Freezing Point	N/A
Boiling Point / Range	107.6°F (42°C)
Vapor Pressure	868 mm Hg @20°C
Partition Coefficient	N/A
Percent volatile	100%
Flammability	N/A
Propellant	HFC-134a
VOC Content	64.7% per US State and Federal Consumer Product Regulations
Color	Colorless
Flash Point	None
Density	N/A
Evaporation Rate	< 1 BuAc
Vapor density	> 1
Auto-Ignition Temperature	860°F (460°C) estimated
Viscosity	<3 cSt @ 25°C
Specific Gravity	1.2 - 1.3 @20°C (water=1)
Dielectric Strength	47,500 V (ASTM D-877)
KB Value	60

DIRECTIONS

Hold can 6-8 inches away and spray directly on surface to clean. While safe to use on most surfaces, test for compatibility in an inconspicuous area before applying generally.

HANDLING

Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection.

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

DISPOSAL

Dispose of contents/container in accordance to local/state/national waste disposal regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
04416	C04416	12 wt oz / 340 g / 279 mL	aerosol	12	13 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved