

HANDLING

- Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

DIRECTIONS

- Test in small inconspicuous area prior to use.
- Apply to surface and allow the staining color/layout fluid to liquify.
- Wipe surface with a cloth or paper towel.

STORAGE

- Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL INFORMATION

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

DISPOSAL INFORMATION

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

FEATURES

- Prepares metal surfaces
- Dries in minutes
- Does not contain toluene or chlorinated solvents



PHYSICAL PROPERTIES

Physical State	Liquid.
Odor	Sweet. Solvent.
Boiling Point	133 °F (56.11 °C)
VOC Content	100 % / 388 g/l
Evaporation Rate	< 1 (BuAc = 1)
Viscosity	Water thin
Prop 65 Warning	YES

AVAILABLE IN

Net Contents	Container Type	Units/Case	Part #
16 oz	aerosol	12	82038
930 mL	bottle	12	82638
1 gal	bottle	4	82738
5 gal	pail	1	82838
55 gal	drum	1	82938