

# Rustlick™ B

## Rust Preventative

### DESCRIPTION

Rustlick™ B Rust Preventative is a non-flammable water-soluble corrosion inhibitor designed to prevent in-process rusting of ferrous metals. It leaves a non-oily, dry, microscopic protective film and can be used for hydrostatic testing and vibratory finishing. Biodegradable, transparent, and non-irritating, Rustlick B is not subject to bacterial decomposition or rancidity and does not require removal prior to painting, plating, or assembly.

### FEATURES

- Use for short-term indoor storage ; prevents flash rusting
- No cleaning required before painting or plating
- Can be used for sand blasting or vibratory finishing

### APPLICATIONS

- For short-term corrosion prevention

### DIRECTIONS

### HANDLING

Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Wear personal protective equipment. Wash thoroughly after handling.

### STORAGE

Keep container tightly closed. Store in original container. Keep locked-up.

### DISPOSAL INFORMATION

This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.



### PROPERTIES

Appearance/physical state	Liquid
Odor	Amine
Melting point/freezing point	No data available
Boiling point/range	212 °F/ 100 °C
Vapor pressure	No data available
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	No data available
Color	Clear blue
Flash point	204°F (96°C)
Relative density	No data available
Evaporation rate	<1
Vapor density	>1
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	1.1
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

### SHELF LIFE INFORMATION

1 year



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved



# Rustlick™ B

## Rust Preventative

---

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
73011	1 gal	container	4	40 lbs
73051	5 gal	pail	1	48 lbs
73551	55 gal	drum	1	522 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved