



STEEL RED™ Layout Fluid

DIRECTIONS FOR USE

- Apply to a surface that is clean, dry and free of oil and grease.

FEATURES

- Steel Red provides a uniform deep color that prevents glare and eye strain.
- Allows for sharp, clear, and precise scribes.
- Provides a thin film without cracking/chipping and adds practically no thickness to work surface.
- Meets A-A 59168 dated 21st May 2014 paragraph 3.1.1 thru 3.2.4.4 with the exception of 3.3(chemical resistance to chlorinated solvents).
- Dries within minutes.
- Reveals defects and pinholes in a variety of surfaces.
- Great for inspection of gear tooth contact patterns.
- Available in multiple package sizes.
- Does not contain any reportable amounts of Xylene.

MATERIALS COMPATIBILITY

- Safe on most surfaces.
- Removable with DYKEM® Remover & Cleaner.
- Surface tests should be run to determine compatibility prior to use.

HEALTH AND SAFETY

- Flammable liquid and vapor. Keep away from heat, sparks and flame. Use only with adequate ventilation. Avoid contact with skin and eyes.



PHYSICAL PROPERTIES

Appearance	Red
Odor	Alcohol
Specific gravity:	<1
VOC level	92% - 94% by weight
Flash point	53°F
Dry Time	< 2 minutes (Note: Drying time may vary depending on film thickness)

AVAILABLE IN

Part #
80096
80296
80396
80496
80696



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved