

# Accu-Lube® Solenoids and Air Filters

## FEATURES

- Solenoids are available as 24VDC, 110VAC, or dual-voltage replacements
- Allows for control of MQL applicators via machine input - turn the flow of lubricant on when in operation and off when the machine stops without manual intervention
- Use of multiple solenoids allows groups of pumps/nozzles to be activated independently
- In-line Air Filter ensures delivery of clean, dry air to the frequency generator and also allows for manual control of incoming air pressure.

## APPLICATIONS

- Where delivery of precise amounts of lubricant to any externally-lubricated application is needed, such as:
  - Milling
  - Drilling
  - Sawing (band & circular)
  - Turning
  - Tapping

## DIRECTIONS

See Accu-Lube Box Applicator installation instructions for installation of replacement and operation of solenoid or air filter

## HANDLING

Follow standard industrial hygiene practices for handling electronic components and fittings.

## STORAGE

Keep in original packaging until ready to install to avoid losing/misplacing fittings or other parts.

## DISPOSAL

Dispose of in accordance with local regulations.



## AVAILABLE PRODUCTS

Part No.	Container Type
9516D	24VDC Control Solenoid
9518	110VAC Control Solenoid
9537	Dual-Power (24VDC/110VAC) Control Solenoid
9396	9396 - Combination Air Filter & Regulator



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved