



Stainless Steel Cleaner

Oil-Based

FEATURES

- Cleans, Polishes, and Preserves the high luster of stainless steel
- Provides a protective coating
- Removes: Spot Marks, Grease, Film, Water Marks, Fingerprints, and more
- Oil-Based Formula

APPLICATIONS

- Aluminum
- Stainless Steel
- Chrome
- Copper and Brass

DIRECTIONS

Shake well before using. Spray directly onto the surface or apply using a clean (damp or dry) cloth.

HANDLING

After skin contact: Immediately wash with water and soap and rinse thoroughly. Wear protective gloves and eye protection.

STORAGE

Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not pierce or burn, even after use. Keep out of reach of children.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.



PROPERTIES

Appearance / Physical State	Aerosol
Odor	Lemon
Melting / Freezing Point	Undetermined
Boiling Point / Range	Not applicable, as aerosol
Vapor Pressure	20 - 35 psig @ 21°C (70°F)
Partition Coefficient	Not determined
Flammability	Not applicable
Propellant	Propane/Isobutane blend
VOC Content	13%
Color	Colorless
Flash Point	82°C (180°F) (liquid component)
Vapor density	> 1 (Air=1)
Auto-Ignition Temperature	Product is not self-igniting
Density	0.80 g/cm (6.676 lbs/gal) @ 20°C (68°F)
Water Solubility	Not miscible

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
20920	16 oz / 454 g	aerosol	12	17 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved