

# Accu-Lube® Stick Lube

## Hand-Applied Lubricant

### FEATURES

- Lubricant stick for rotating or stationary cutting tools
- Reduces heat build-up
- Vegetable-based

### APPLICATIONS

- Short-run machining
- Rotating or stationary cutting tools
- Belt, disc and wheel grinding
- Ferrous & nonferrous metals, aluminum and titanium

### DIRECTIONS

Apply sparingly, directly on the tool.

### HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

### STORAGE

Keep container tightly closed in a dry and well-ventilated place.

### DISPOSAL INFORMATION

Dispose of in accordance with local regulations.



### PHYSICAL PROPERTIES

Appearance/physical state	Solid
Odor	Mild
Melting point/freezing point	110-120°F/43-49°C
Boiling point/range	> 400°F/>204°C
Vapor pressure	< 1 mmHg
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	None
Color	Blue
Flash point	> 200°F/>93°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	>1
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.86
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
79042	2.2 oz	Push-up stick	24	6 lbs.
79045	13 wt. oz	Stick	24	23 lbs.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved