



Strong Steel Stick Renewal Composite



FEATURES

- Hardens like steel in 60 minutes
- Can be machined, drilled, tapped and painted in 60 minutes
- Plugs and seals leaks; Non-rusting

APPLICATIONS

- Custom Formed Gaskets
- Electrical Equipment
- Ductwork

SPECIFICATIONS AND APPROVALS

- NSF/ANSI/CAN 61

PROPERTIES

Evaporation Rate	>1 BuAC = 1
Water Solubility	Immiscible

HANDLING

Safe Handling

Avoid skin contact, including inhalation.
Wear protective clothing when risk of exposure occurs.
Use in a well-ventilated area.
Avoid contact with incompatible materials.
When handling, DO NOT eat, drink or smoke.
Keep containers securely sealed when not in use.
Avoid physical damage to containers.
Always wash hands with soap and water after handling.
Work clothes should be laundered separately. Launder contaminated clothing before re-use.
Use good occupational work practice.
Observe manufacturer's storage and handling recommendations contained within the SDS.
Establish good housekeeping practices.
Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.
Use continuous suction at points of dust generation to capture and minimize the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimize the probability of a 'secondary' explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.
Do not use air hoses for cleaning.
See the SDS for Other Information

STORAGE

Suitable Container

Generally packaging as originally supplied with the manufactured item is sufficient to protect against physical hazards.

Storage Incompatibility

Under normal conditions of storage and use, hazardous reactions will not occur.

DISPOSAL

DO NOT allow wash water from cleaning or process equipment to enter drains.
It may be necessary to collect all wash water for treatment before disposal.
In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
Where in doubt contact the responsible authority.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
60159	C60159	4 wt oz / 114 g	tube	36	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved