

Accu-Lube® Synthetic II

General Purpose MQL

FEATURES

- Economical, water-based minimum quantity lubricant with non-chlorinated extreme pressure and boundary additives for moderate-duty near-dry stamping and machining.

APPLICATIONS

- Stamping
- General machining, sawing and cutting
- Economical
- Water-based, synthetic lubricant
- Provides excellent corrosion protection
- Boron free with superior lubricity
- For ferrous & nonferrous metals and aluminum
- Clean before heat treating with rinse water

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wear protective gloves/protective clothing/eye protection/face protection.

STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

DISPOSAL

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	Mild
Melting / Freezing Point	No data available
Boiling Point / Range	100°C
Vapor Pressure	No data available
Partition Coefficient	No data available
Percent volatile	No data available
Flammability	No data available
Propellant	N/A
VOC Content	No data available
Color	Light amber
Flash Point	> 100°C
Density	No data available
Evaporation Rate	No data available
Vapor density	No data available
Auto-Ignition Temperature	No data available
Viscosity	No data available
Specific Gravity	1.05
Temperature Range	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LBSY201	1 gal	bottle	4	36 lbs
LBSY255	55 gal	drum	1	499 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved