



# T-91™

## Non-Solvent Degreaser



### FEATURES

- Ideal for traditional solvent cleaning, plastic basin style part washers and dip tanks
- VOC compliant in all 50 states
- Zero VOCs: VOC's per CARB/OTC/ LADCO: 0 g/L, VOC content per SCAQMD: 0 g/L
- Biodegradable
- Efficient: requires less product than traditional solvents to get the job done
- pH = 9-10
- Contains no solvents
- Moderate foam for effective mechanical cleaning

### APPLICATIONS

- Basin style parts washer
- Bilges
- Compressors
- Concrete
- Dip Tanks
- Drill presses
- Engines
- Floors
- Forklifts
- Grease traps
- Machinery
- Marine
- Tanks
- Tools
- Walls

### SPECIFICATIONS AND APPROVALS

- NSF International, A1

### PROPERTIES

<b>Appearance / Physical State</b>	Liquid
<b>Odor</b>	Mild soapy
<b>Melting / Freezing Point</b>	Not available.
<b>Boiling Point / Range</b>	Not available
<b>Vapor Pressure</b>	18 mm Hg
<b>Partition Coefficient</b>	< 0
<b>Percent volatile</b>	85-87%
<b>Flammability</b>	Not established
<b>Propellant</b>	Not applicable
<b>VOC Content</b>	0 % per State and Federal Consumer Product Regulations
<b>Color</b>	Colourless to light yellow
<b>Flash Point</b>	None
<b>Density</b>	8.67 lb/gal
<b>Evaporation Rate</b>	1 BuAc (Water = 1)
<b>Vapor density</b>	Not established
<b>Auto-Ignition Temperature</b>	Not established
<b>Viscosity</b>	Not established
<b>Specific Gravity</b>	1.03
<b>Temperature Range</b>	Not applicable
<b>4-Ball Weld Load</b>	Not applicable
<b>Water Solubility</b>	100%

### DIRECTIONS

(Trigger) Turn nozzle to spray or stream position. Pull trigger to spray. Then agitate surface with a brush cloth or wipe. Remove soils by wiping. Rinse with water for residue free surface. NOTE: Test for compatibility on sensitive materials. Do not heat above 175°F (79°C). Do not allow parts to soak longer than 24 hours. As a direct solvent degreaser replacement: Use T-91 undiluted (straight) as a direct solvent replacement for all heavy duty degreasing applications. Dilution Ratio Product: (as a neutral pH cleaner) Water Water Applications: (Suggested dilution ranges for cleaning surfaces not damaged by water alone)  
 1:10 - 1:75 Floors: Light to Heavy Duty Cleaning/Degreasing  
 Undiluted to 1 : 10 Metals: Heavy Duty Cleaning/Degreasing  
 1:20 - 1:80 Plastics, rubbers & painted surfaces  
 1:50 - 1:100 Glass  
 1:10 - 1:80 Pressure Washing: Light to Heavy-Duty Cleaning/Degreasing  
 1:10 - 1:25 Soak Tanks [Do Not Exceed 140°F (60°C)]

### HANDLING

Observe good industrial hygiene practices

### STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### DISPOSAL

Waste from residues / unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
06328	C06328	28 fl oz / 828 mL	trigger	12	27 lbs
06301	C06301	1 gal / 3.78 L	bottles	4	38 lbs
06355	C06355	55 gal / 208 L	drum	1	535 lbs
06330		330 gal / 1249 L	tote	1	2968 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved