

## HANDLING

- Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

## STORAGE

- Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

## DISPOSAL

- Dispose of in accordance with local/regional/national regulations.

## FEATURES

- Ideal for transmission and engine marking that won't chip off
- Resistant to most coolants and cutting fluids
- Permanent ink writes on smooth surfaces such as metal, aluminum, steel, plastics, cardboard, and more
- Drying Time: 25 – 35 seconds



## PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Odor	Mild. Pungent.
Flash Point	57°F (14°C)
Boiling Point / Range	242°F (116.5°C)
VOC Content	87 - 90%
Water Solubility	Immiscible
Prop 65 Warning	Yes

## AVAILABLE IN

Color	Marker Tip	Units/Case	Part #
red	medium, felt (#38)	48	44819
yellow	medium, felt (#38)	48	44401
white	medium, felt (#38)	48	44175
green	medium, felt (#38)	48	44177
blue	medium, felt (#38)	48	44179
black	medium, felt (#38)	48	44203