

HANDLING

- Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and
- sources of ignition. Take precautionary measures against static discharges. Use only in an
- area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of
- vapors by static electricity discharge, all metal parts of the equipment must be grounded.
- Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld
- containers.

STORAGE

- Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

DISPOSAL INFORMATION

- Dispose of in accordance with local/regional/national regulations.

FEATURES

- Ideal for transmission and engine marking that won't chip off
- Resistant to most coolants and cutting fluids
- Permanent ink writes on smooth surfaces such as metal, aluminum, steel, plastics, cardboard, and more
- Drying Time: 25 - 35 seconds



PHYSICAL PROPERTIES

| | |
|------------------|--------------------|
| Physical State | Liquid. |
| Odor | Pungent, mild |
| Flash Point | 15.56 °C / 60 °F |
| Boiling Point | 117.22 °C / 243 °F |
| VOC Content | 86.1% 757 g/L |
| Evaporation Rate | > 1 (air = 1) |
| Vapor Density | > 1 (air = 1) |
| Prop 65 Warning | YES |

AVAILABLE IN

| Color | Marker Tip | Units/Case | Part # |
|--------|------------------|------------|--------|
| red | threaded cap tip | 12 | 44819 |
| yellow | threaded cap tip | 12 | 44401 |
| White | Threaded Cap Tip | 12 | 44175 |
| Green | Threaded Cap Tip | 12 | 44177 |
| Blue | Threaded Cap Tip | 12 | 44179 |
| Black | Threaded Cap Tip | 12 | 44203 |