



Tapmatic® Edge Crème



FEATURES

- Safe on all metals
- Ecological and economical
- Does not contain any hazardous chemicals
- For use when drilling, tapping blind holes, forming, bending, pre-coating fasteners, and lubricating rubber seals
- Squeeze tube allows easy application
- Excellent for vertical applications

APPLICATIONS

- Boring
- Broaching
- Drilling
- Engraving
- Grinding
- Tapping
- Drawing
- Facing
- Reaming
- Milling
- Threading
- Turning

SPECIFICATIONS AND APPROVALS

- Delta Airlines
- Ford Motor Co.
- General Motors Co.

PROPERTIES

Appearance / Physical State	Viscous Paste. Solid
Odor	Slight. Soapy
Melting / Freezing Point	Not established
Boiling Point / Range	631.4°F (333°C) (estimated)
Vapor Pressure	Not established
Partition Coefficient	Not established
Percent volatile	15 - 16%
Flammability	Not established
Propellant	N/A
VOC Content	0 % per State and Federal Consumer Product Regulations
Color	Opaque.
Flash Point	> 199.40°F (> 93.00°C) Tag Closed Cup
Density	Not established
Evaporation Rate	Not established
Vapor density	Not established
Auto-Ignition Temperature	Not established
Viscosity	Not established
Specific Gravity	0.87 - 0.89 @ 20°C
Temperature Range	Not established
4-Ball Weld Load	Not established

DIRECTIONS

Apply a few drops of creme prior to contact.

HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Do not get this material on clothing. Do not use in areas without adequate ventilation. Wear personal protective equipment. Observe good industrial hygiene practices. Wash thoroughly after handling. Use care in handling/storage.

STORAGE

Keep tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Use care in handling/storage.

DISPOSAL

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
43100	C43100	10 fl oz / 0.296 L	tube	10	7 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved