



# Transparent Staining Color

## HANDLING

- Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

## STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## DISPOSAL

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

## FEATURES

- Perform well on light and dark tinted metals
- Provide excellent coverage properties and opacity
- Thickness can be adjusted by adding DYKEM® Thinner & Remover
- Fast drying
- Resists cracking, chipping, flaking or scaling
- Will not interfere with moving parts when applied thin



## PHYSICAL PROPERTIES

|                             |                               |
|-----------------------------|-------------------------------|
| Appearance / Physical State | Liquid.                       |
| Odor                        | Sweet, Solvent.               |
| Flash Point                 | 53.0 °F (11.7 °C)             |
| Boiling Point / Range       | 170 - 257 °F (76.67 - 125 °C) |
| VOC Content                 | 87.21%, 753 g/L               |
| Evaporation Rate            | < 1 (BuAc = 1)                |
| Vapor Density               | > 1 (air = 1)                 |
| Prop 65 Warning             | YES                           |

## AVAILABLE IN

| Net Contents | Container Type | Color             | Units/Case | Case Weight | Part # |
|--------------|----------------|-------------------|------------|-------------|--------|
| 1 gal        | bottle         | transparent black | 4          | 32 lbs      | 81731  |



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved