



# TriFree Brake Cleaner



## FEATURES

- Instantly removes brake fluid, grease and oil from brakes
- Improves brake performance
- Helps stop disc brake squeal
- Powerful jet spray and high solvency
- Can be applied without disassembling the brake unit
- No ozone depleting chemicals
- Fast evaporating
- Does not contain chlorinated solvents
- No rinsing
- No residue

## APPLICATIONS

- Brake backing plates
- Brake cylinders
- Brake drums
- Brake linings
- Brake rotors
- Disc brake pads

## PROPERTIES

<b>Appearance/physical state</b>	Gas / Aerosol
<b>Odor</b>	Ether-like/Fruity
<b>Melting point/freezing point</b>	Not established
<b>Boiling point/range</b>	> 132.8°F (> 56°C)
<b>Vapor pressure</b>	> 75 mm Hg @ 20°C
<b>Partition coefficient</b>	Not established
<b>Percent volatile</b>	100%
<b>Flammability limit</b>	Flammability limit - lower (%) 1.2% Flammability limit - upper (%) 12.8%
<b>Propellant</b>	Carbon dioxide
<b>VOC Content</b>	45% per U.S. State and Federal Consumer Product Regulations
<b>Color</b>	Clear/Colorless
<b>Flash point</b>	1.4°F (-17.0 °C) Tag Closed Cup
<b>Relative density</b>	Not established
<b>Evaporation rate</b>	0.1 (BuAc = 1)
<b>Vapor density</b>	- 3 (air = 1)
<b>Auto-ignition temperature</b>	Not established
<b>Viscosity</b>	Not established
<b>Specific Gravity (water=1)</b>	0.75 - 0.77 @ 20°C
<b>Solubility (water)</b>	55% w/w
<b>Temperature Range °F(°C)</b>	Not available
<b>4-Ball Weld Load</b>	Not applicable

## DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

## HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat and sources of ignition. (See Section 7 of the SDS)

## DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

## AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
03620	C03620	15 wt. oz./425 g/544 mL	Aerosol	12	15.0 lbs.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved