



ULTRACUT[®] PRO

Water-Soluble Oil

DESCRIPTION

Ultracut PRO Water-Soluble Oil is a premium water-soluble oil cutting & grinding fluid with chlorinated extreme-pressure additives for heavy-duty machining.

FEATURES

- Premium water-soluble oil
- Chlorinated EP additives
- Increases sump life
- Extends tool life
- Provides corrosion protection
- Excellent lubricity
- Provides great workpiece quality

APPLICATIONS

- Heavy-duty machining and grinding

MATERIALS COMPATIBILITY

- Ferrous and Non-Ferrous Metals
- Aluminum
- Brass, Bronze, and Copper
- Not recommended for Titanium

DIRECTIONS

FOR PRODUCT/APPLICATOR TROUBLE SHOOTING:
Use a refractometer to measure coolant concentration.
Use Triadine 20 or Grotan for microbial control of this fluid in sump tanks. Call Technical Sales for detailed questions pertaining to the products.



PROPERTIES

Appearance / Physical State	Golden yellow to light brown
Class	Water-soluble oil
pH Value	10
Specific Gravity	0.98
Density	8.2 lbs/gal
Flash Point	> 200°F (93°C)
Total chlorine	4.7%
Mineral Oil	53.5%
Water Solubility	Soluble
Dilution Ratio	Light-Duty Machining: 30:1 (3%) Moderate-Duty Machining: 20:1 (5%) Heavy-Duty Machining: 10:1 (10%)
Refractometer Readings	10:1=9.2 20:1=4.6 30:1=3.1

SHELF LIFE INFORMATION

1 year

AVAILABLE PRODUCTS

Part No.	Net Contents	Units/Case
84405	5 gal	1
84455	55 gal	1



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved