



VS 160-30 Stamping Lube

Metal Mates VS-160-30 is a medium duty lubricant for stamping, piercing and punching.

FEATURES

- Universal for wide range of parts
- Easily cleaned weld without wash

APPLICATIONS

- Spray, brush, roll coat or drip. Good on multiple substrates, please call for consultation on specific applications.

DIRECTIONS

Dilute Metal Mates VS with water to suit the specific application. Slowly add water to lubricant while mixing. Water quality enhances the performance of all water-dilutable lubricants.

HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

DISPOSAL INFORMATION

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



PROPERTIES

| | |
|-------------------------|--------------------------------------|
| Odor | mild |
| pH at 10% | 8.0-9.0 |
| Specific Gravity | 0.99 |
| Flash Point | >200F (>93C) |
| Boiling Point | 212F (100C) |
| Melting Point | 212F (100C) |
| Vapor Pressure | <1 |
| Vapor Density | Heavier than air |
| Prop 65 Warning | No |
| Chlorine | Y |
| Dilution Ratios | Typical Dilution 3:1 to 6:1 (33-17%) |

AVAILABLE PRODUCTS

| Part No. | Container Type | Units/Case | Color |
|----------|----------------|------------|--------------|
| MM1002 | 5 gal pail | 1 | creamy white |
| MM1003 | 55 gal drum | 1 | creamy white |
| MM1006 | 330 gal tote | 1 | creamy white |



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved